C&C Rig Dimensions

STAINLESS STEEL COMPONENTS, MAST AND BOOM DIMENSIONS, MAINSAIL CUTBACKS, SPINNAKER POLE TRACK														
Model	Pulpits Fore & Aft		Stanchion	Mast Dimensions	Slug Or Bolt Rope Size	Top of Sail Entry Slot above Black Band	Boom Dimension	Slug/Bolt Rope Size	Tack Pin Cutback	Tack Pin	Clew Pin Cutback	Clew Pin Ht.	Spinnaker Track	Spin. Track Length
C&C 25	1"	1"	1"	6-1/4" x 3-1/8" rect.	5/8"	1'0"	3-1/2 "x 2" rect.	"	1-3/4" std 2- 3/8" opt.	1-1/4"	N/A	N/A	I-1/4" x3/16" tee	6'0"
C&C 27	1″	1″	1″	5-3/4" x 3-7/8"	3/4" Slide or 3/8" Rope	12"	4-7/8" x 3-1/2"	3/8"	1-1/2"	1-1/2"	Slug	N/A	5/8" x 1-3/8" Internal	
C&C 29	1″	1″	1″	6" x 4" D-shape	"	1'0"	4-1/2" x 2-3/4" oval	н	1-1/2″	1-1/2″	N/A	N/A	1-1/4"x3/16"	7'0"
C&C 30	1″	1″	1″	8" x 4-1/2" rect.	"	5"	6-1/4" x 3-1/8" rect.	"	2-1/8"	1-1/8"	1"	2-1/2"	1-1/4″x3/16"	6'0"
C&C 32	1″	1″	1″	7-3/4" x 4-5/8" diamond	н	1′0″	6-1/4"x 3-1/8" rect.	n	2-1/8"	1-1/8"	1"	2-1/2"	1-1/4"x 3/16" tee	8'6"
C&C 34	1″	1″	1″	7-3/4" x 4-5/8" diamond	"	1 ¹ 0"	6-1/4" x 3-1/8" rect.	"	2-1/8"	1-1/8"	1"	2-1/2"	1-1/4"x 3/16" tee	8'6"
C&C 35	1″	1″	1″	7-3/4" x 4-5/8" diamond	"	1'0"	6-1/4" x 3-I/8" rect.	"	1-1/2″	1-1/2″	1"	N/A	1-1/4"x 3/16" tee	9'0"
C&C 37	1″	1"	1″	9" x 5-3/8" diamond	"	1'0"	6-1/4" x 3-I/8" rect.	1/2"	2-1/8"	1-1/8"	1"	2-1/2"	1-1/4"x 3/16" tee	9'0"
C&C 40& AC40	1"	1"	1"	10" x 5-3/8" diamond	5/8"	1'0"	7-1/2" x 4" oval	5/8"	2"	2-1/4″	Slug	N/A	1-1/4"x 3/16" tee	11'0"

C&C YACHTS Note: All cutback dimensions are taken from the appropriate 'P' and 'E' limits.